

Flow Measurement SITRANS F US Clamp-on

SITRANS FUE1010 (Energy)

Standard MLFB for quick delivery on SITRANS FUE1010 (Energy system)

Selection and Ordering data	Article No.	Order code
SITRANS FUE1010 (Energy)	7ME350 - - 0	+ +
Design		
Dedicated		
IP65 (NEMA 4X) wall mount	0	K 0 2 + K 0 2 + R 0 2
Portable		
IP40 (NEMA 1) Battery powered	2	K 0 1 + K 0 1 + R 0 1
Number of channels/ultrasonic paths		
Dedicated meters		
Single channel	1	
Portable meters		
Dual channel/Dual path	4	
Flowmeter functions and I/O configurations		
• Portable Standard I/O	C	
- Energy efficiency COP/EER output		
- 2x 4-20mA analog input		
• Dedicated Standard I/O	F	
- Reflexor Capability		
- Energy efficiency COP/EER output		
- 2x 4-20mA analog input		
Meter power options		
90 ... 240 V AC (Dedicated only)	A	
Charger Type A for Europe (CEE7/7)	C	
Charger Type K for U.S. (NEMA 5-15P)	G	
No charger	J	
Communication options		
RS 232 (standard)	0	
RTD temperature sensor pair		
No RTDs (Note: Temperature input is required for Energy systems)	0	
1 x Pair Std clamp-on RTD (NEMA 4X only) ³⁾	1	
2 x Pair Std clamp-on RTD (For Dual Channel NEMA 4X only) ³⁾	2	
1 x Pair Std clamp-on RTD (For NEMA 12 Portable) ³⁾	3	
2 x Pair Std clamp-on RTD (For Dual Channel NEMA 1 Portable) ³⁾	4	
1 x Insertion RTD with Thermowell and Lagging		M 1 A
2 x Insertion RTD with Thermowell and Lagging		M 1 B
Sensor for channel 1 (includes pipe mounting kit and spacer bar for indicated max. OD listed) See "Sensor selection charts" for specifications.		
no sensor		A
A2 universal Trackmount and straps provided up to 75 mm (3")		B
B3 universal Trackmount and straps provided up to 125 mm (5")		C
C3 universal Mounting frame and straps provided up to 300 mm (13")		D
D3 universal Mounting frame and straps provided up to 600 mm (24")		E
E2 universal Mounting frame and straps provided up to 1200 mm (48") ¹⁾⁴⁾		F
C1H (high precision) Mounting frame and straps provided up to 1200 mm (48") ⁴⁾		M
C2H (high precision) Mounting frame and straps provided up to 1200 mm (48") ⁴⁾		N
D1H (high precision) Mounting frame and straps provided up to 1200 mm (48") ⁴⁾		P
D2H (high precision) Mounting frame and straps provided up to 1200 mm (48") ⁴⁾		Q
Doppler to 12" with strap kit (not for IP65 (NEMA7)), for up to 121 °C (250 °F)		S
D1H High temperature range 104 °C/220 °F HP ²⁾		Z
		P 1 P

3

Flow Measurement

SITRANS F US Clamp-on

SITRANS FUE1010 (Energy)

3

Selection and Ordering data	Article No.	Order code
SITRANS FUE1010 (Energy)	7ME350 - - 0	+ +
Sensor for channel 2 (includes pipe mounting kit and spacer bar for indicated max. OD listed) See "Sensor selection charts" for specifications. no sensor		A B C D E F M N P R S Z
A2 universal Trackmount and straps provided up to 75 mm (3")		
B3 universal Trackmount and straps provided up to 125 mm (5")		
C3 universal Mounting frame and straps provided up to 300 mm (13")		
D3 universal Mounting frame and straps provided up to 600 mm (24")		
E2 universal Mounting frame and straps provided up to 1200 mm (48") ¹⁾⁴⁾		
C1H (high precision) Mounting frame and straps provided up to 1200 mm (48") ⁴⁾		
C2H (high precision) Mounting frame and straps provided up to 1200 mm (48") ⁴⁾		
D1H (high precision) Mounting frame and straps provided up to 1200 mm (48") ⁴⁾		
D4H (high precision) Mounting frame and straps provided up to 1200 mm (48") ⁴⁾		
Doppler to 12" with strap kit (not for IP65 (NEMA7)), for up to 121 °C (250 °F)		
D1H High temperature range 104 °C/220 °F HP ²⁾		Q1P
Approvals UL/Portable		0
FM, CSA, CE, Dedicated		1

- 1) Supplied spacer bar supports pipes up to 1050 mm (42 inch). For pipes larger than 1050 mm (42 inch) purchase also, spare part 7ME3960-OMS40 (1012BN-4)
- 2) Supplied spacer bar supports pipes up to 750 mm (30 inch). For pipes larger than 750 mm (30 inch) purchase also, spare part 7ME3960-OMS40 (1012BN-4)
- 3) Requires two R** cables per one RTD pair
- 4) 600 mm (24") for portable systems only

Standard MLFB product offering represents 4 to 6 weeks delivery time
For sensor and RTD cables for quick delivery see tables at end of section

Flow Measurement SITRANS F US Clamp-on

SITRANS FUE1010 (Energy)

3

Selection and Ordering data	Article No.	Ord. code	Selection and Ordering data	Article No.	Ord. code
SITRANS FUE1010 (Energy)			SITRANS FUE1010 (Energy)		
<ul style="list-style-type: none"> Dedicated IP65 (NEMA 4X) wall mount 	7ME3500-		<ul style="list-style-type: none"> Dedicated IP65 (NEMA 4X) wall mount 	7ME3500-	
<ul style="list-style-type: none"> Portable IP40 (NEMA 1) Battery powered 	7ME3502-		<ul style="list-style-type: none"> Portable IP40 (NEMA 1) Battery powered 	7ME3502-	
		- 0			- 0
Number of channels/ultrasonic paths			RTD temperature sensor		
Dedicated meter			(includes mounting hardware for pipes above 1.5" outer diameter)		
Dedicated meter			No RTDs (Note: temperature input is required for energy system)	0	
Single channel	1		1 x pair standard clamp-on RTD (NEMA 4X only) ²⁾	1	
Dual channel/Dual path	2		2 x pair standard clamp-on RTD (for dual channel NEMA 4X only) ²⁾	2	
Portables			1 x pair standard clamp-on RTD (NEMA 1 Portable) ²⁾	3	
Dual channel/Dual path	4		2 x pair standard clamp-on RTD (for dual channel NEMA 1 Portable) ²⁾	4	
Flowmeter functions and I/O configurations			1 x Insertion style RTD with thermowell and lagging ²⁾	9	M 1 A
<ul style="list-style-type: none"> Portable Standard I/O <ul style="list-style-type: none"> Reflexor capability Graphic display 2 x 0 ... 10 V 2 x 4 ... 20 mA 2 x pulse output 4 x status logic Energy efficiency COP/EER output 2 x 4 ... 20 mA analog input 	C		2 x Insertion style RTD with thermowell and lagging ²⁾	9	M 1 B
<ul style="list-style-type: none"> Dedicated Standard I/O <ul style="list-style-type: none"> Reflexor capability Graphic display 2 x 0 ... 10 V 2 x 4 ... 20 mA 2 x pulse output 4 x relay C type Energy efficiency COP/EER output 2 x 4 ... 20 mA analog input 	F				
<ul style="list-style-type: none"> Extended output adder plus standard inputs (4 additional 4 ... 20 mA outputs) and form C relay 	Z	J 1 B	Sensor for channel 1		
			Including pipe mounting tracks for sizes A & B sensors indented for pipe with a OD less than 125 mm (5") and mounting frame/spacer bars for sizes C, D & E sensors. Straps provided are for the indicated maximum OD listed below. Strap kits are available to accommodate larger pipes (refer to spare part list). Refer to "Sensor Selection Charts" for the sensor suitability of pipe size and wall thickness.		
Meter power options			No sensor		A
90 ... 240 V AC (Dedicated only)	A		A2 universal Trackmount and straps provided up to 75 mm (3")		B
9 ... 36 V DC (Dedicated only)	B		B3 universal Trackmount and straps provided up to 125 mm (5")		C
Charger Type A for Europe (CEE77)	C		C3 universal Mounting frame and straps provided up to 300 mm (13")		D
Charger Type C for Australia (AS3112)	D		D3 universal Mounting frame and straps provided up to 600 mm (24")		E
Charger Type D for U.K. (BS1363)	E		E2 universal Mounting frame and straps provided up to 1200 mm (48") ¹⁾³⁾		F
Charger Type J for Japan (JIS8303)	F				
Charger Type K for U.S. (NEMA 5-15P)	G		For the following A1H to D4H sensors, temperature range is -40 °C ... 65 °C (-41 °F ... 150 °F), nominal 21 °C (70 °F):		
Charger Type L for Switzerland (SEV1011)	H		For other temperature ranges please see spare parts list.		
No Charger	J		A2H (high precision) Trackmount and straps provided up to 75 mm (3")		H
External 4 hours battery with US plug for Portable	Z	K 1 A	A3H (high precision) Trackmount and straps provided up to 75 mm (3")		J
External 4 hours battery with European plug for Portable	Z	K 1 B	B1H (high precision) Trackmount and straps provided up to 125 mm (5")		K
Communication options					
RS 232 (standard)	0				
Standard MODBUS configurations include Baudrate: 9600, Parity: None, Stop Bits: 1, Data bits: 8, MODBUS data: 16 bit, Data format: word normal, Mode: RTU, and MODBUS format: Gould. For other configurations please select option 9 and L1Y and state requirements in plain text					
MODBUS Single and Dual Channel	1				
MODBUS Dual Path	2				
Other Version, MODBUS, N2, Other Baud Rate, Other Parity, State in Plain Text	9				

1) Supplied spacer bar supports pipes up to 1050 mm (42 inch). For pipes larger than 1050 mm (42 inch) purchase also, spare part 7ME3960-0MS40 (1012BN-4).
 2) Requires two R** cables per one RTD pair
 3) 600 mm (24") for portable systems only

Flow Measurement

SITRANS F US Clamp-on

SITRANS FUE1010 (Energy)

3

Selection and Ordering data		Article No.	Ord. code	Selection and Ordering data		Article No.	Ord. code
SITRANS FUE1010 (Energy)				SITRANS FUE1010 (Energy)			
• Dedicated IP65 (NEMA 4X) wall mount		7ME3500-		• Dedicated IP65 (NEMA 4X) wall mount		7ME3500-	
• Portable IP40 (NEMA 1) Battery powered		7ME3502-		• Portable IP40 (NEMA 1) Battery powered		7ME3502-	
		■ ■ ■ ■ ■ - 0 ■ ■ ■ ■ ■				■ ■ ■ ■ ■ - 0 ■ ■ ■ ■ ■	
Sensor for channel 1 (continued)				Sensor for channel 2 (continued)			
B2H (high precision)	Trackmount and straps provided up to 125 mm (5")		L	For the following A1H to D4H sensors, temperature range is -40 °C ... 65 °C (-41 °F ... 150 °F), nominal 21 °C (70 °F):			
C1H (high precision)	Mounting frame and straps provided up to 1200 mm (48") ²⁾³⁾		M	A2H (high precision)	Trackmount and straps provided up to 75 mm (3")		H
C2H (high precision)	Mounting frame and straps provided up to 1200 mm (48") ²⁾³⁾		N	A3H (high precision)	Trackmount and straps provided up to 75 mm (3")		J
D1H (high precision)	Mounting frame and straps provided up to 1200 mm (48") ²⁾³⁾		P	B1H (high precision)	Trackmount and straps provided up to 125 mm (5")		K
D2H (high precision)	Trackmount and straps provided up to 1200 mm (48") ²⁾³⁾		Q	B2H (high precision)	Trackmount and straps provided up to 125 mm (5")		L
D4H (high precision)	Trackmount and straps provided up to 1200 mm (48") ²⁾³⁾		R	C1H (high precision)	Mounting frame and straps provided up to 1200 mm (48") ²⁾³⁾		M
Doppler	to 12" with strap kit, for up to 121 °C (250 °F)		S	C2H (high precision)	Mounting frame and straps provided up to 1200 mm (48") ²⁾³⁾		N
High temperature sensor size 2 for up to 230 °C (446 °F) (30 ... 200 mm diam. (1.18 ... 7.67 inch diam.))		Z	P 1 A	D1H (high precision)	Mounting frame and straps provided up to 1200 mm (48") ²⁾³⁾		P
High temperature sensor size 3 for up to 230 °C (446 °F) (150 ... 610 mm diam. (5.90 ... 24 inch diam.))		Z	P 1 B	D2H (high precision)	Mounting frame and straps provided up to 1200 mm (48") ²⁾³⁾		Q
High temperature sensor size 4 for up to 230 °C (446 °F) (400 ... 1200 mm diam. (15.75 ... 47.25 inch diam.))		Z	P 1 C	D4H (high precision)	Mounting frame and straps provided up to 1200 mm (48") ²⁾³⁾		R
For the following B1H to D4H sensors, temperature range is -1 °C up to 104 °C (30 °F up to 220 °F), nominal 65 °C (150 °F):				Doppler	to 12" with strap kit, for up to 121 °C (250 °F)		S
B1H (high temperature range HP)		Z	P 1 K	High temperature sensor size 2 for up to 230 °C (446 °F) (30 ... 200 mm diam. (1.18 ... 7.67 inch diam.))		Z	Q 1 A
B2H (high temperature range HP)		Z	P 1 L	High temperature sensor size 3 for up to 230 °C (446 °F) (150 to 610 mm diam. (5.90 to 24 inch diam.))		Z	Q 1 B
C1H (high temperature range HP)		Z	P 1 M	High temperature sensor size 4 for up to 230 °C (446 °F) (400 to 1200 mm diam. (15.75 to 47.25 inch diam.))		Z	Q 1 C
C2H (high temperature range HP)		Z	P 1 N	For the following B1H to D4H sensors, temperature range is -1 °C up to 104 °C (30 °F up ... 220 °F), nominal 65 °C (150 °F):			
D1H (high temperature range HP) ²⁾		Z	P 1 P	B1H (high temperature range HP)		Z	Q 1 K
D2H (high temperature range HP) ²⁾		Z	P 1 Q	B2H (high temperature range HP)		Z	Q 1 L
D4H (high temperature range HP) ²⁾		Z	P 1 R	C1H (high temperature range HP)		Z	Q 1 M
Sensor for channel 2				C2H (high temperature range HP)		Z	Q 1 N
(includes pipe mounting kit for indicated max. outer diameter listed) See "Sensor selection charts" for specifications.				D1H (high temperature range HP) ²⁾		Z	Q 1 P
no sensor			A	D2H (high temperature range HP) ²⁾		Z	Q 1 Q
A2 universal	Trackmount and straps provided up to 75 mm (3")		B	D4H (high temperature range HP) ²⁾		Z	Q 1 R
B3 universal	Trackmount and straps provided up to 125 mm (5")		C				
C3 universal	Mounting frame and straps provided up to 300 mm (13")		D	Approvals			
D3 universal	Mounting frame and straps provided up to 600 mm (24")		E	FM/CSA/CE Dedicated		1	
E2 universal	Mounting frame and straps provided up to 1200 mm (48") ¹⁾³⁾		F	UL/ULc/CE Portable		0	
				1) Supplied spacer bar supports pipes up to 1050 mm (42 inch). For pipes larger than 1050 mm (42 inch) purchase also, spare part 7ME3960-0MS40 (1012BN-4).			
				2) Supplied spacer bar supports pipes up to 750 mm (30 inch). For pipes larger than 750 mm (30 inch) purchase also, spare part 7ME3960-0MS40 (1012BN-4).			
				3) 600 mm (24") for portable systems only			

Flow Measurement

SITRANS F US Clamp-on

SITRANS FUE1010 (Energy)

Selection and Ordering data

Order code

Further designs

Please add "-Z" to Article No. and specify Order code(s).

Cable assembly for sensors (add for # of channels) See "Sensor cable selection chart"	K..
Cable assembly for RTDs (add for # of RTDs) See "RTD cable selection chart"	R..
Cable termination kit (for one cable pair) dedicated only	
• Termination for standard, plenum and armored sensor cable	T01
• Termination for submersible sensor cable	T11
• RTD cable termination kit for standard RTD	T21
• RTD cable termination kit for submersible RTD	T31
• Insert RTD cable termination kit	T41
Wet flow transfer calibration (priced on request)	
6 point calibration 2/water (Price per channel)	
• 2SS40 pipe	D01
• 3CS40 pipe	D02
• 4CS40 pipe	D03
• 4SS40 pipe	D04
• 6CS40 pipe	D05
• 6SS40 pipe	D06
• 6CS120 pipe	D07
• 8CS40 pipe	D08
• 8SS40 pipe	D09
• 8CS120 pipe	D10
• 10CS Standard pipe	D11
• 10CS40 pipe	D12
• 10SS40 pipe	D13
• 12CS Standard pipe	D14
• 12CS40 pipe	D15
• 14CS30 pipe	D16
• 14CS40 pipe	D17
• 16CS Standard pipe	D18
• 16CS40 pipe	D19
• 18CS Standard pipe	D20
• 20CS20 pipe	D21
• 20CS30 pipe	D22
• 24CS Standard pipe	D23
• 24CS20 pipe	D24
• 24CS30 pipe	D25
• 30CS Standard pipe	D26
• 36CS Standard pipe	D27
• Other pipe, other liquid, additional points, witness	Y28
Tag name plate	
• Stainless steel tag with 3.2 mm (0.13 inch) character size (68 characters max.)	Y19

MLFB example

Application example

A dedicated clamp-on energy meter is required for two separate return lines. Both will use clamp-on RTDs for the supply and return lines. AC power is available and data access will be via MODBUS communication.

Pipe 1 is a DN150 (6") schedule 40 carbon steel line

Pipe 2 is a DN 300 (12") ductile iron line

MLFB Article No.: **7ME3500-2DA10-2NE0-Z**
K03 + K05 + R03 + R05 + R02 + R03

Selection and Ordering data

Article No.

Ord. code

Selection and Ordering data	Article No.	Ord. code
SITRANS FUE1010 meter family	7ME3500-2DA10-2NE0-Z	
IP65 (NEMA 4X) enclosure	0	
Dual channel	2	
Dedicated Type 1 I/O option	D	
90 ... 230 V AC power option	A	
MODBUS option	1	
2 pairs of clamp-on RTDs	2	
Sensor code for 6" pipe	N	
Sensor code for 12" pipe	E	
No approval required	1	
30 m (100 ft) sensor cable for channel 1		K 0 3
61 m (200 ft) sensor cable for channel 1		K 0 5
30 m (100 ft) cable for RTD 1		R 0 3
61 m (200 ft) cable for RTD 2		R 0 5
15 m (50 ft) cable for RTD 3		R 0 2
30 m (100 ft) cable for RTD 4		R 0 3

Selection and Ordering data

Order code

Selection and Ordering data	Order code
Operating Instructions for SITRANS FUE1010	
English NEMA 4X Wall mount	A5E03086491
German NEMA 4X Wall mount	A5E03086492
English IP40 NEMA 1 Battery powered	A5E02951524
German IP40 NEMA 1 Battery powered	A5E02951536

This device is shipped with a Quick Start Guide and a CD containing further SITRANS F literature.

All literature is also available for free at:

<http://www.siemens.com/flowdocumentation>